

Center Disc Design Butterfly Valve



(A) Center Disc Butterfly Valve

Size : 2" (50 mm) to 36" (900 mm)
 Class : PN 16 upto 12" and above PN 10
 End : Wafer Type / Lug Type / Flange Ends
 Design : API-609 - Category : A
 Seat : Moulded Seat as NBR / EPDM / SILICON / VITON / PTFE
 Operation : Lever / Gear / Actuator / Electric Operated
 *Special Material & Higher Size also available on request.

(B) Offset Disc Butterfly Valve

Size : 2" (50 mm) to 36" (900 mm)
 Class : PN 10 / PN 16
 End : Wafer Type / Lug Type / Flange Ends
 Design : API-609 - Category : B / AWWA C504
 Seat : Moulded Seat Lip Seal Design
 NBR / EPDM / SILICON / VITON etc.
 Operation : Lever / Gear / Actuator / Electric Operated

SIZE	VALVE DIMENSION									TOP PLATE DRILLING			WEIGHT* kg.
	A	B	C	D	F	G	H	KEY WAY	Q	PCD	N	N	
40	40	77	85	34	31.7	12.7	8	-	22	70	4	9	2.7
50	50	95	100	43	31.7	14.2	9.5	-	26	70	4	9	3
65	65	117	115	46	31.7	14.2	9.5	-	47	70	4	9	4.1
80	75	126	125	46	31.7	14.2	9.5	-	60	70	4	9	4.7
100	100	160	150	53	31.7	15.9	11	-	85	70	4	9	5.9
125	125	182	155	56	31.7	15.9	11	-	113	70	4	9	7.8
150	152	210	170	56	31.7	19	12.7	-	144	102	4	11	13
200	203	265	205	61	31.7	22.2	18.5	-	195	102	4	11	18
250	252	325	255	69	50	28.6	-	6.3X6.3	245	125	4	11	23.4
300	300	366	275	78	50	28.6	-	6.3X6.3	313	125	4	11	40
350	337	438	305	78	65	35	-	7.9X7.9	330	140	4	18	57
400	387	490	335	102	65	41.2	-	9.5X9.5	376	140	4	18	78
450	438	539	368	114	65	47.6	-	12.7X9.5	425	140	4	18	101
500	489	595	400	127	65	47.6	-	12.7X9.5	475	140	4	18	134
600	587	696	495	154	75	47.6	-	12.7X9.5	570	165	4	18	225